




Shunt release, 110-415V, 1HP

Part no. ZP-ASA/230
Catalog No. 248439

EL-Nummer (Norway) 1609471

Delivery program

Basic function			Accessories for miniature circuit-breaker Accessories for combined residual-current/power circuit-breakers
Basic function accessories			Shunt release
Application			Switchgear for industrial and advanced commercial applications
Product range			Accessory
Side mounting			for fitting on left to: FAZ, FRBmM-1N, Z-MS
Contact sequence			

Technical data

Electrical

Rated operational voltage	U_e	V AC	60
Voltage range		V AC	110-415
Voltage range		V DC	110-220
Rated impulse withstand voltage	U_{imp}	kV	2.5

Mechanical

Mounting width		mm	17.5 (1 MU)
Degree of protection			
Integrated			IP40
Terminals			Open Mouth/Lift
Tightening torque of terminal screws		Nm	≤ 2.4

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])			
Device fitting			Other
Additional equipment			Shunt release (for power circuit breaker)
Installed at the factory			No
Width in number of modular spacings			1
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	0

Rated voltage	V	230
Voltage type for actuating		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		1
Suitable for max. current main contact unit	A	2.1

Dimensions

