



Control switch 11 S, 1 N/C, 16A, 250 V

Part no. Z-SW/SO
 Catalog No. 276302

Design verification as per IEC/EN 61439

| Technical data for design verification | | | |
|--|-----------|---|----|
| Rated operational current for specified heat dissipation | I_n | A | 16 |
| Heat dissipation per pole, current-dependent | P_{vid} | W | 2 |
| Equipment heat dissipation, current-dependent | P_{vid} | W | 4 |

Technical data ETIM 8.0

| Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545) | | | |
|--|--|----|----------------|
| Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ec1@ss10.0.1-27-14-23-01 [AFZ813014]) | | | |
| Switching function | | | Control switch |
| Number of contacts as normally open contact | | | 1 |
| Number of contacts as normally closed contact | | | 1 |
| Number of contacts as change-over contact | | | 0 |
| Number of poles | | | 2 |
| Rated current | | A | 16 |
| Rated voltage | | V | 250 |
| Min. rated voltage | | V | 230 |
| Rated switching capacity | | kA | 0.02 |
| Short-circuit breaking capacity (I _{cw}) | | kA | 0.02 |
| Voltage type | | | AC |
| With signal lamp | | | No |
| Colour calotte | | | Other |
| Lamp type | | | Other |
| Lamp socket | | | Other |
| Max. lamp power | | W | 0 |
| Width in number of modular spacings | | | 1 |
| Built-in depth | | mm | 60 |
| Degree of protection (IP) | | | IP40 |
| Imprint/indication | | | Other |
| Forced segregation (according to DIN VDE 0113) | | | No |