



Switch with LED, 230AC/DC, 1N/0+1N/C, 16A, orange, 1HP

Part no. Z-SWL230/SO  
 Catalog No. 276307

**Design verification as per IEC/EN 61439**

Technical data for design verification			
Rated operational current for specified heat dissipation	$I_n$	A	16
Heat dissipation per pole, current-dependent	$P_{vid}$	W	2
Equipment heat dissipation, current-dependent	$P_{vid}$	W	4

**Technical data ETIM 8.0**

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecl@ss10.0.1-27-14-23-01 [AFZ813014])			
Switching function			Control switch
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of poles			2
Rated current		A	16
Rated voltage		V	250
Min. rated voltage		V	230
Rated switching capacity		kA	0.02
Short-circuit breaking capacity ( $I_{cw}$ )		kA	0.02
Voltage type			AC
With signal lamp			Yes
Colour calotte			Other
Lamp type			LED
Lamp socket			Other
Max. lamp power		W	2
Width in number of modular spacings			1
Built-in depth		mm	80
Degree of protection (IP)			IP40
Imprint/indication			Other
Forced segregation (according to DIN VDE 0113)			No