



CRC BIKE OIL

Ref. : 10235

1. GENERAL DESCRIPTION

Multi-purpose service spray for bicycles.

A multi-purpose lubricant that penetrates through rust and corrosion, displaces water and cleans away scale and dirt. CRC Bike Oil is based on a paraffin oil and a multiple organic inhibitor system that prevents rust and corrosion by forming a continuous protection barrier against water and oxygen.

2. FEATURES

- Penetrates quickly, even into the finest pores and cracks of the surface.
- Lubricates and restores smooth action.
- Displaces moisture, especially after cleaning parts with water.
- Loosens rusted parts and makes them work again.
- Stops annoying squeaks.
- Leaves a thin film that protects metals from corrosion induced by humidity and other corrosive atmospheres.
- Easy repair by eliminating the need for disassembly.
- Compatible with O-ring chains.
- Safe for all metals and alloys.
- Safe on painted surfaces, coatings, plastics and rubbers (if in doubt, test prior to use).
- Aerosols are equipped with the 360° (upside-down) spray valve and extension tube for added convenience.
- Aerosols are pressurised with non-flammable CO₂ propellant, giving an active product content of over 95% (i.e. over 30% more than typical hydrocarbon propelled products).

3. APPLICATIONS

- Lubrication of all moving parts, such as chains, shifting gears, brake mechanisms, pedals, etc.
- Winter-storage of bicycles and parts.

4. DIRECTIONS

- Apply generously on all moving parts.
- Repeat regularly to ensure perfect maintenance at all times.
- Before each application clean parts to be treated thoroughly with CRC Quickleen.
- If necessary, to be removed by CRC Quickleen.
- A safety data sheet (MSDS) according EU directive 93/112 is available for all CRC products.



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC BIKE OIL

Ref. : 10235

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	: light amber, clear liquid
Specific gravity @ 20°C	: 0,84
Freezing point	: < -10°C
Flash point closed cup	: 73°C
Viscosity @ 20°C	: 9 mPa.s
Temperature resistance	: 100 °C
Distillation range	: 180 - 500 °C
Ultimate film thickness (@ 20°C, after a 24 h spread)	: 1 to 2 µm
Maximum expected coverage (@ 20°C, after a 24 h spread)	: 50 - 80 m ² /l
Spread (25 µl, after a 24 h spread)	: 104 cm ²
Non-volatiles (6 h, 100 °C)	: 56 %

6. PACKAGING

Aerosol: 24 x 200 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10235 03 1200 03
Date : 27 January 2012



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

