



## CRC CONTACT PROTECT

Ref. : 10706

### 1. GENERAL DESCRIPTION

---

Contact Protect is a mix of protective oil in a solvent, specially designed to protect electric contacts against corrosion. CRC Contact Protect also has a good lubrication action, and reduces the susceptibility to wear of sliding and push/pull contacts.

When the contacts are corroded, use CRC Oxide Clean to renovate the contacts, prior to CRC Contact Protect.

### 2. FEATURES

---

- Evaporates quickly and leaves a protective film.
- Protects the contacts against future corrosion.
- Lubricates the contacts, thus preventing wear.
- Convenient 360° (upside-down) spray valve for aerosols.

### 3. APPLICATIONS

---

- Bulb fittings in the illumination system of cars, trucks, busses, trailers, caravans, tractors,...
- Push-pull connectors used in protected environments for connecting wires in the automotive sector.
- Contact points in connection plugs used to branch electric or electronic modules.
- Clamps for fuses.
- Contactors.
- Contact pins on printed circuits.

### 4. DIRECTIONS

---

- Do not use on energized equipment.
- Spray a thin film of CRC Contact Protect on the clean contacts.
- Move the contact points a few times, whenever possible.
- Allow the solvents to evaporate before energizing.
- A safety data sheet (MSDS) according EU93/112 is available for all CRC products.

### 5. TYPICAL PRODUCT DATA (Without propellant)

---

Flash point	(ASTM D 56)	:	< 0°C
Specific gravity	@ 20°C (FEA 605)	:	0,76 g/cm <sup>3</sup>
Appearance		:	blue transparent
Evaporation rate	(DIN 53 170 – ether =1)	:	± 5



Manufactured by :  
CRC Industries Europe NV  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
www.crcind.com





## CRC CONTACT PROTECT

Ref. : 10706

### 6. PACKAGING

---

Aerosol: 6 x 200 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10706 03 1201 02  
Date : 23 september 2003



Manufactured by :  
CRC Industries Europe NV  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

