

TECHNICAL DATA

1/2

CRC ACRYL RAL HIGH TEMP

Ref. : 40206

1. GENERAL DESCRIPTION

CRC Acryl Ral High Temp is an acrylic based paint, delivered in an aerosol can, in two colors: black and silver.

2. FEATURES

- Fast drying.
- Resists to extreme high temperatures till 690°C
- Excellent flexibility
- Once the paint is polymerized, it has a high UV resistance
- Good adhesion on metal, wood, glass, paint-able plastics, concrete, stone
- Does not contain any heavy metals
- Good covering ability
- Long lasting, intensive shine

3. APPLICATIONS

CRC Acryl Ral High Temp is recommended as a protecting paint for all kind of repair of lacquered surfaces which will be exposed to heat, in:

- Industry
- Automotive
- Home and garden

4. DIRECTIONS


- Shake aerosol can very well for at least two minutes after agitator ball is free. Repeat frequently while using.
- Apply to a clean, degreased, dry surface for best results. Remove rust and scale with a wire brush.
- Use the can in an upright position.
- Apply in light, even coats; best results are obtained with 2 – 3 lighter rather than 1 heavy coat. Additional coats can be applied after 3 - 5 minutes but not longer as 30 minutes.
- When spraying is finished, clean aerosol valve by turning can upside down and press button until only propellant escapes. If clogging occurs, remove button and clean orifice with fine wire.
- Do not use on energized equipment. Use in well ventilated area.

A safety data sheet (MSDS) according to EC Regulation N°1907/2006 Art.31 and amendments is available for all CRC products.



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





TECHNICAL DATA 2/2

CRC ACRYL RAL HIGH TEMP

Ref. : 40206

5. TYPICAL PRODUCT DATA (without propellant)

Resin type	:	Silicone
Color	:	Black and silver
Gloss (60° angle)	:	flat : 15 ± 5 E
	:	Glossy : 85 ± 5 E
Particle size	:	< 10 µ
Drying time (20°C ; 50%RH)	:	dust free : < 10 min to touch : < 20 min to handle: < 60 min
Over paint-able	:	after 5 min
Adhesion (Gt)	:	0 – 1
Temperature resistance	:	690°C

6. PACKAGING

Aerosol: 400 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 40206 03 0211 01
Date : 09 March 2011



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

