

# Product data sheet XLED curved

## XLED curved

Attractive buildings need attractive floodlights.

### Technical data

|                           |                                                            |
|---------------------------|------------------------------------------------------------|
| Dimensions (HxWxD):       | 120 x 160 x 107 mm                                         |
| Voltage:                  | 230-240V, 50/60Hz                                          |
| Output:                   | 10,5 W                                                     |
| Luminous flux/efficiency: | 690 lm, 65,7 lm/W                                          |
| Colour temperature:       | 4000K neutralwhite, SDCM 4                                 |
| LED lifetime:             | 50.000 hours (L70B10)                                      |
| Sensor technology:        | Passive infrared                                           |
| Angle of detection:       | 160°                                                       |
| Reach:                    | 8m max.                                                    |
| Response light level:     | 2 - 1000 Lux                                               |
| Time setting:             | 2s – 70 Min.                                               |
| IP-/protection class:     | IP 44/ I                                                   |
| Own power consumption:    | 0,15W                                                      |
| Material:                 | Aluminium, UV-resistant plastic                            |
| Dimensions packaging:     | 225 x 121 x 222 mm                                         |
| Customs tariff number:    | 94051021                                                   |
| Country of origin:        | Germany (start of production), Romania (serial production) |
| Region of origin:         | 14 (start of production), 03 (serial production)           |



Keine Druckversion! Bitte kontaktieren Sie uns für ein druckbares Produktbild.